

ADSL2+

4 Ethernet Port | USB Host | 802.11n

AR-5381u

Wireless Router



The AR-5381u is a high performance 802.11n, 4-port Ethernet ADSL2+ Router with full routing capabilities to segment and route IP protocol. It features TR-069/098/111 and TR-068 compliance for hassle-free setup and configuration. It is best suited for residential or small office environments that need high speed internet access.

FEATURES

Fast Connections

ADSL2/2+ carries WAN traffic at speeds of up to 24 Mbps. Wireless 802.11n supports speeds up to 300Mbps, while Ethernet ports supports LAN traffic at 100Mbps. An USB host (2.0) port is also included. The TR-068 compliant interfaces and LED indicators simplify installation and improve ease-of-use.

Reliability and Quality

For over 20 years, Comtrend has delivered superior quality products to our customers worldwide. Every product goes through rigorous testing and is backed by 2 year warranty.

Quality Of Service

Classify, control, and prioritize diverse traffic types, for pristine video, toll-quality voice, and error-free data transmissions.

Safe & Secure Connections

As the first level of protection, a Stateful Firewall (with DoS protection) and NAT/PAT help to isolate the LAN from external threats. IP and MAC address filtering provide fine-grained access control to or from the network. Advanced security technologies, such as Virtual Private Networks (VPN) with PPTP pass-through, L2TP pass-through and IPSec pass-through ensure secure networking, and WPA/WPA2/802.1x/WEP guarantee rock-solid security for wireless connections.

Remote Management

TR-069/TR-098/TR-111 standards compatibility ensures interoperability with central office remote management equipment. From the user perspective this reduces downtime and frustration. For the service provider it means improved customer relations and cost savings. Other management options include telnet, ssh and a web user interface with advanced functionality.

AR-5381U

4 Ethernet Port | USB Host | 802.11n



SPECIFICATIONS

Hardware

- RJ-11 X1 for ADSL2/2+
- RJ-45 X 4 for LAN, (10/100 BaseT auto-sense)
- WPS button X1
- Wi-Fi On/Off button X1
- Reset Button X 1
- Power switch X 1
- USB host X 1

WAN

- Comply with ITU-T G.992.5, ITU-T G.992.3, ITU-T G.992.1, ANSI T1.413 Issue 2, AnnexM
- G.992.5 (ADSL2+)
Downstream : 24 Mbps Upstream : 1.3 Mbps
- G.992.3 (ADSL2)
Downstream : 12 Mbps Upstream : 1.3 Mbps
- G.DMT
Downstream : 8Mbps Upstream : 832Kbps

LAN

- IEEE 802.3, IEEE 802.3u
- Support MDI/MDX
- Multiple Subnets on LAN

Wireless

- IEEE802.11b/g/n
- 64, 128-bit Wired Equivalent Privacy (WEP) Data Encryption
- 11 Channels (US, Canada)/ 13 Channels (Europe)/ 14 Channels (Japan)
- Up to 300Mbps data rate
- Multiple BSSID
- MAC address filtering, WDS, WEP, WPA, WPA2, IEEE 802.1x
- 10,25,50,100mW@22MHz channel bandwidth output power level can be selected according to the environment

ATM Attributes

- RFC 2364 (PPPoA), RFC 2684 (RFC 1483) Bridge/Route; RFC 2516 (PPPoE); RFC 1577 (IPoA)
- Support up to 16 PVCs
- AAL5
- UBR/CBR/VBR-rt/VBR-nrt
- UNI 3.1/4.0
- OAM F4/F5

PTM Attributes

- Dual Latency

Management

- TR-069/TR-098/TR-104/TR-111, SNMP, Telnet, Web-based management, Configuration backup and restoration
- Software upgrade via HTTP, TFTP server, or FTP server

Security Functions

- PAP, CHAP, Packet and MAC address filtering, SSH
- VPN termination
- Three level login including local admin, local user and remote technical support access

Power Supply

- 100 Vac -240 Vac, 12Vdc/1.0A

Networking Protocols

- RFC2684 VC-MUX, LLC/SNAP encapsulations for bridged or routed packet
- RFC2364 PPP over AAL5
- IPoA, PPPoA, PPPoE, Multiple PPPoE sessions on single PVC, PPPoE pass-through, PPPoE filtering of on-PPPoE packets between WAN and LAN
- Transparent bridging between all LAN and WAN interfaces
- 802.1p/802.1q VLAN support
- Spanning Tree Algorithm
- IGMP Proxy V1/V2/V3, IGMP Snooping V1/V2/V3, Fast leave
- Static route, RIP v1/v2, ARP, RARP, SNTP
- DHCP Server/Client/Relay,
- DNS Relay, Dynamic DNS,
- IPv6 subset

QoS

- Packet level QoS classification rules,
- priority queuing using ATM TX queues,
- IP TOS/Precedence,
- 802.1p marking,
- DiffServ DSCP marking
- Src/dest MAC addresses classification.

Firewall/Filtering

- Stateful Inspection Firewall
- Stateless Packet Filter
- Day-time Parental Control
- URI/URL filtering
- Denial of Service (DOS): ARP attacks, Ping attacks, Ping of Death, LAND, SYNC, Smurf, Unreachable, Teardrop
- TCP/IP/Port/interface filtering rules Support both incoming and outgoing filtering

NAT/NAPT

- Support Port Triggering and Port forwarding
- Symmetric port-overloading NAT, Full-Cone NAT
- Dynamic NAPT (NAPT N-to-1)
- Support DMZ host
- Virtual Server
- VPN Passthrough (PPTP, L2TP, IPSec)

Application Layer Gateway (ALG)

- SIP, H.323, Yahoo messenger, ICQ, RealPlayer, Net2Phone, NetMeeting, MSN, X-box, Microsoft DirectX games and etc

Environment Condition

- Operating temperature: 0 ~ 40 degrees Celsius
- Relative humidity: 5 ~ 95% (non-condensing)

Dimensions

158mm(W) X 40mm(H) X 136mm(D)

Kit Weight

1*AR-5381u, 1*RJ11 cable, 1*RJ45 cable, 1*power adapter, 1*CD-ROM = 0.9 kg

Note: Specifications are subject to change without notice



COMTREND CORPORATION

Taiwan:

3F-1, No.10, Lane 609, Chung Hsin Road Section 5, San Chung, Taipei, Taiwan 24159
Tel: 886-2-2999-8261
Fax: 886-2-2999-8497

China:

NO.88 East QianJin Road,Kunshan City,JiangSu,China
Tel: 86-512-57383156, 86-512-57383157, 86-512-57384515
Fax: 86-512-57383155

Spain:

Edif. América II C/Prócion,7 portal 3 bajo H 28023 Madrid, Spain
Tel: 34-917990403
Fax: 34-913510999

UK:

566 Chiswick High Road Building 3, Chiswick Park Chiswick - London, W4 5YA UK
Tel: 44-0-8453701031
Fax: 44-0-8453701032

France:

87, Rue du Gouverneur Général Félix Eboué 92130 Issy-les-Moulineaux, France
Tel: 33-1-70715700
Fax: 33-1-70715701

Czech Republic:

TOKOVO Jankovcova 1518/2, 170 00, Prague 7, Czech Republic
Tel: 420-266-782040
Fax: 420-266-782990

USA & Canada:

16 Goodyear, Suite 120, Irvine, CA 92618
Tel: 1-949-7539640
Fax: 1-949-7539020

Brazil:

Al. Campinas, 977 - 7º. Floor - Room 71 / 72 - Jardins
Zip Code: 01404-001 - São Paulo - SP - Brazil
Tel: 00 55 11 3052-2295
Fax: 00 55 11 3052-2295